

JALWENGE SAS

00JJE70

Softane

Adventure

S3 CI SRC
EN ISO 20345:2011
38 to 47



QuickLio™

0%
METAL



- Water-repellent full-grain leather
- Dual density **Softane™** sole
- Polymère toe cap type B and no metallic midsole
- Antistatic and amagnétique

- Safety shoe rangers type with minimal stitching for improved resistance. Black color.
- Water-repellent full grain leather upper, thickness 1.9/2.1 mm. Black colour.
- Pu reinforcement to the front of the sole.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded ergonomic collar in compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Padded leather tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Lace up by five pairs of non-metallic lace-stays and two pairs of **Quick LIO** (Quick Lace In Out).
Water-repellent laces : 130 cm.
- Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- Antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- 100% composite materials: lighter than steel, amagnetic, non-conductive of heat and cold.
- Heel stiffener to reinforce the heel seat.
- Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement **SRC** (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,30** (>0,18) – On the heel: **0,28** (>0,13)

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorbtion > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1716 g / Net weight (42) : 1500 g
Size	38 à 47
Packaging	5 paires
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 343



 **Jallatte**®

www.jallatte.com