

JALPOLE SAS
00JJS11

Softane™
Avant-Garde

S3 CI WR SRC
EN ISO 20345:2011
37 to 48



- Full grain **AP 23** leather
- **Softane™** dual-density sole
- Polymère toe cap type **B** / Antiperforation rustproof steel
- Antistatic

- ❖ Natural-coloured, fur-lined boot with 2 leather side tabs for rapid pull-on
- ❖ Upper in water and oil resistant full grain **AP 23** leather, exclusive to Jallatte
 - ❖ **10 to 15%** (2.4 mm) **thicker** than most leathers used for safety footwear.
 - ❖ **Resistance to penetration of water vapour three times higher** than the minimum fixed by European Standard.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Flat binding at top of quarters.
- ❖ **GORE-TEX®** Performance Comfort footwear membrane for a perfect thermic microclimate in every weather condition.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ **Stainless rustproof steel midsole.**
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Dual-density **Softane™** sole with progressive heel shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability.

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,38** (>0,32) – On the heel **0,30** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,19** (>0,18) – On the heel: **0,14** (>0,13)

- ❖ Density of comfort layer = 0.45 / Density of wearing layer = 1.10
- ❖ Heel shock absorption 30 Joule
- ❖ Wrap-around profile for better stability when walking
- ❖ Highly resistant to oil and hydrocarbons
- ❖ Abrasion resistance 75 mm3
- ❖ Stainless steel midsole



 **Jallatte®**

www.jallatte.com

Weight	Gross weight (42) : 1668 g / Net weight (42) : 1360 g
Size	37 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345

Non contractual document
Copyright JALLATTE
Limited distribution

04/06/2024