

Jallatte® GORE-TEX®

JALTEX SAS JJV53

S3 CI WR SRC
EN ISO 20345:2011
38 to 47



- Water-repellent full-grain leather
- Dual density **Softane™** sole
- Polymère toe cap and no metallic midsole
- Antistatic and amagnétique

- ❖ High-laced boot style outdoor. Brown and black color.
 - ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Optimal breathability and unmatched watertightness.**
 - ❖ Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
 - ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
 - ❖ Fastened by 5 pairs of no metalics lace stays. Laces 120 cm 38 to 41 and 130 cm 42 to 47
 - ❖ Padded, "3D' lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
 - ❖ Tabs at the back for easy pull-on.
 - ❖ **GORE-TEX®** Performance Comfort Footwear membrane.
 - ❖ **Polyjal** inlay covering the entire surface of the foot, antistatic, with heel cushioning
 - ❖ Heel stiffener to reinforce the heel seat
 - ❖ Ergonomic shoe, with broad synthetic polymer toe cap **SPRINGTANE** , for saving on weight (50% lighter than steel). Impact resistance to 200 Joules.
 - ❖ New manufacturing **process** : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- 100% composite** materials: lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ Dual density **Softane™** PU sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,30** (>0,18) – On the heel: **0,28** (>0,13)

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorbtion > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1682 g / Net weight (42) : 1464 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359



 **Jallatte®**

www.jallatte.com