

## JALACCOLON SAS JMI02

**S3 SRC**  
**EN ISO 20345:2011**  
**39 to 47**



- Full grain leather
- Dual density Softane™ sole
- Antistatic and non-magnetic

- ❖ Black moccasin type shoe.
- ❖ Finest quality water-resistant leather upper, 1.9/2.1 mm thick.
- ❖ Padded top of upper, in soft compact foam.
- ❖ Quarters lined in "3D" knit. A three-dimensional fabric combining foam for protection and comfort, and an open honeycomb structure for ventilation around the foot.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Ergonomic shoe, with broad synthetic polymer toecap, for saving on weight (50% lighter than steel) . Impact resistance to **200 Joules**
- ❖ New manufacturing process: inner sole and insert in **FlexTane™ By Jallatte** perforation resistant material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- ❖ Inlay under the entire foot, removable, antistatic, anatomical fit and absorbs heel impacts. Highly capable of absorbing and evaporating perspiration.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Sole in dual-material **Softane™** fitted with progressive effect shock absorber protecting the back and joints from vibrations.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,48** (>0,32) – On the heel **0,37** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,25** (>0,18) – On the heel: **0,16** (>0,13)

- ❖ Comfort layer, density = 0.45
- ❖ Wear layer, density = 1.10
- ❖ Heel shock absorber 27 Joules
- ❖ Very high level of resistance to oils and hydrocarbons
- ❖ Abrasion resistance 90 mm<sup>3</sup>

Weight	Gross weight (42) : 1193 g / Net weight (42) : 975 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359

