

# JALGAHERIS SAS

## 00JMJ04

**Softane™**  
Prestige

**S3 SRC**  
**EN ISO 20345:2011**  
**38 to 47**



- Full grain leather
- Dual density Softane™ sole
- Antistatic and non-magnetic

- ❖ Low Derby type shoe, black colour.
- ❖ Upper in finest quality water-resistant leather, 2.0/2.2 mm thick.
- ❖ Quarters lined in "3D" knit. A three-dimensional fabric combining foam for protection and comfort, and an open honeycomb structure for ventilation around the foot.
- ❖ Vamp lined with non-woven fabric, resistant to abrasion and acid perspiration.
- ❖ Tongue in finest quality leather with 3D lining, combined with two side gussets to prevent grit from getting into the shoe.
- ❖ Collar padded with dense flexible foam.
- ❖ Laces up with 4 pairs of non-metallic eyelets. Black laces : 90 cm.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- ❖ **Ergonomic shoe**, with **broad synthetic polymer toecap type B**, for **saving on weight (50% lighter than steel)**. Impact resistance to **200 Joules**. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ **New manufacturing process**: inner sole and insert in **FleXtane™ By Jallatte** perforation resistant material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Sole in dual-material **Softane™** fitted with progressive effect shock absorber protecting the back and joints from vibrations.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,45** (>0,32) – On the heel **0,33** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,20** (>0,18) – On the heel: **0,14** (>0,13)

- ❖ Comfort layer, density = 0.45.
- ❖ Wear layer, density = 1.10.
- ❖ Heel shock absorber 25 Joules
- ❖ Very high level of resistance to oils and hydrocarbons.
- ❖ Abrasion resistance 70 mm3.



 **Jallatte®**

www.jallatte.com

|                |   |                 |                 |                 |
|----------------|---|-----------------|-----------------|-----------------|
| Weight         | Gross weight (42) : 1404 g / Net weight (42) : 1188 g |                 |                 |                 |
| Size           | 35 to 39  | 40              | 41 to 45        | 46 to 47        |
| Packaging      | 5 pairs   | 10 pairs        |                 | 5 pairs         |
| Box shoes (mm) | 306 x 192 x 114                                       |                 | 340 x 210 x 133 |                 |
| Cartons (mm)   | 590 x 210 x 320                                       | 590 x 410 x 320 | 685 x 440 x 359 | 685 x 225 x 359 |