

## JALGERAINT SAS JMJ06

**S3 SRC**  
**EN ISO 20345:2011**  
**35 to 47**



- **Full grain leather**
  - **Dual density Softane™ sole**
  - **Antistatic and non-magnetic**
- ❖ Heavy-duty boot, colour black.
  - ❖ Upper finest quality water-resistant leather, thickness 2.0/2.2 mm.
  - ❖ Ergonomic collar padded with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
  - ❖ Quarters lined in "3D" – a knitted three-dimensional fabric combined with foam for protection and comfort, and an open honeycomb structure for ventilation around the foot.
  - ❖ 3D" textile inner lining of the quarters and bellows tongue, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
  - ❖ Vamp lining in non-woven fabric. Resists scuffing and acid perspiration.
  - ❖ Tongue in padded suede to give better protection to the instep, combined with two side gussets to prevent grit from getting inside the shoe.
  - ❖ Fastens with 6 pairs of non-metallic eyelets. Black laces : 120 cm.
  - ❖ **Ergonomic shoe**, with **broad synthetic polymer toecap**, for **saving on weight (50% lighter than steel)**. Impact resistance to **200 Joules**.
  - ❖ **New manufacturing process**: inner sole and insert in **FleXtane™ By Jallatte** perforation resistant material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
  - ❖ Inlay covering the entire surface of the foot, removable, antistatic, anatomical and with heel cushioning.
  - ❖ Heel stiffener to reinforce the heel seat.

Sole in dual-material **Softane™** fitted with progressive effect shock absorber protecting the back and joints from vibrations.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,45** (>0,32) – On the heel **0,33** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,20** (>0,18) – On the heel: **0,14** (>0,13)

- ❖ Comfort layer, density = 0.45.
- ❖ Wear layer, density = 1.10.
- ❖ Heel shock absorber 25 Joules
- ❖ Very high level of resistance to oils and hydrocarbons.
- ❖ Abrasion resistance 70 mm<sup>3</sup>.



Weight	Gross weight (42) : 1558 g / Net weight (42) : 1332 g			
Size	35 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359