

00JN120
JALCROSS ESD

J-NUDE 2



S3S FO SR
EN ISO 20345:2022
35 to 47



Link-ESD



- **Leather pull-up upper / waterproof textile**
- **J-nude 2 PU/ PU sole**
- **Amagnetic and dissipative**
- **Type B and non-metallic anti-perforation tip S**

- ❖ Low safety shoe type urban sport, black color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- ❖ Water-repellent leather upper with a pull up finish. Upper and inserts in water-repellent technical textile.
- ❖ Reflective heel insert and lace ups for good night visibility.
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Closure system by lacing on 2 pairs of non-metallic eyelets and 2 reflective textile loops. Loop black color 100 cm.
- ❖ **Soft + Gel** footbed made of **BASF Dynamic PU with** heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™ system**, static electricity dissipater.
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ **Ergonomic shoe** with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.
- ❖ **The FleXtane™ S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.

Slip resistance tests results EN Standard ISO
20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,35** ($\geq 0,31$)
B- Front to back **0,40** ($\geq 0,36$)

Additional requirement **SR** : Ceramic /Glycerin

C - Heel to the front **0,22** ($\geq 0,19$)
D- Front to back **0,27** ($\geq 0,22$)

Innovative sole all in flexibility, bi-component **Softane/TPU** for natural foot movement.

- Gridded outsole for natural foot movement.
- High slip resistance with the grooves in the front and the back of the sole.



Weight	Gross weight (42) : 1382 g / Net weight (42) : 1174 g			
Size	35 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130	
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356