

00JNI26

# JALCATCH SAS ESD

# J-nude 2

S1P SRC  
EN ISO 20345:2011  
35 to 47



0%  
METAL

Link-ESD



- **Synthetic nubuck / Textil**
- **Suole J-nude 2 PU / PU**
- **Safety toe cap type B and midsole no metallic**
- **Antistatic and dissipative**

- ❖ Low safety shoe, urban sport type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.
- ❖ Synthetic nubuck, Inserts and collar in technical textiles . Color grey / black. Silkscreened Jallatte applies.Pu reinforcement to the front of the sole.
- ❖ Breathable upper lining in **3D mesh**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on 1 pair of eyelets and 3 pairs of fabric loops . Lace-loop keeps tongue in place as you walk. Black laces : 100 cm.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative multi-contact static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided
  - for a **SECOSOL®** orthopaedic insole.
- ❖ Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ New manufacturing process : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
  - **100% composite** materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ Heel stiffener to reinforce the heel seat.



**Slip resistance tests results**  
EN Standard : EN ISO 20345 : 2011  
**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,47** (>0,32) – On the heel **0,34** (>0,28)

**SRB** Test ground steel/lubricant : glycerine  
On flat **0,33** (>0,18) – On the heel **0,21** (>0,13)

**Suole PU / PU de BASF®**, for natural foot movement :

- **New PU by BASF® for more flexibility and lightness.**
- Gridded outsole for natural foot movement.
- High slip resistance with the grooves in the front and the back of the sole.



Weight	Gross weight (42) : 1323 g / Net weight (42) : 1115 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359