



- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather upper. Fluorescent markings on the back of the heel. Black color.
- Lining of the quarters in **OVER DRY** technical textile, very resistant and highly breathable.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on 5 pairs of non metal eyelets and 2 pairs of hooks **Quick Lio (maintain the lace in place and allows quick lacing and unlacing)**. Black laces 160 cm.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative multi-contact, static electricity dissipater. (Patent pending).
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard **22568-4 : 2021**.
- **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J



- **BASF® PU/PU** sole with an urban sport design, linear profile and excellent slip resistance.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,47** (>0,32)-On the heel **0,34** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,33** (>0,18)-On the heel **0, 21** (>0,13)

| | | | | |
|-----------------|---|-----------------|-----------------|-----------------|
| Weight | Gross Weight (42) : 1496 g / Net Weight (42) : 1290 g | | | |
| Size | 35 to 39 | 40 to 41 | 42 to 45 | 46 to 48 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box (mm) | 340 x 210 x 133 | | 340 x 245 x 133 | |
| Dimensions (mm) | 685 x 225 x 359 | 685 x 440 x 359 | 685 x 505 x 359 | 685 x 255 x 359 |