



S3S CI FO SR
EN ISO 20345:2022
35 to 48

Low urban sport shoe
Dissipative



- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- Full-grain leather upper with a grained, water-repellent appearance. Reflective insert at the heel. Black.
- Lining of the quarters in **OVER DRY** technical textile, very resistant and highly breathable.
- Non-woven textile forefoot lining.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection. Closing by lacing on 5 pairs of non-metallic eyelets. Black lace 120 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™system**, an innovative and seamless, multi-contact, static electricity dissipater.
- **The FLEX-SYSTEM® S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- **LIGHT-PLUS® B** safety end cap made of synthetic material protecting against a 200 J impact. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.



- **BASF® PU/PU sole** with an urban sport design, linear profile and excellent slip resistance.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,35** ($\geq 0,31$)

B- Front to back **0,40** ($\geq 0,36$)

Additional requirement SR : Ceramic /Glycerin

C - Heel to the front **0,22** ($\geq 0,19$)

D- Front to back **0,27** ($\geq 0,22$)

Weight	Gross Weight (42) : 1422 g / Net Weight (42) : 1213 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359