

KARINA ESD ARAR402

S1P CI SRC EN ISO 20345:2011 35 to 42

FLEX

Urban sport style safety shoe Dissipative

ALULITE"

SOFT





- e Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.
- **@** Suede leather. Perforated quarters and top of upper for better foot ventilation. Grey color.
- e Breathable upper lining in **3D** mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.

3DLining

- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❷ Lace up on 5 pairs of metal eyelets. Two laces 100 cm pink and grey.
- Soft footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted.
- FLEX-SYSTEM[®] Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 22568-4: 2021.
- **ALU-LITE**[®] tip in aluminium resisting an impact of an energy of 200 joules.

Slip resistance tests resultsEN Standard : EN ISO 20345 : 2011Requirement SRC (SRA+SRB)SRA Test ground : ceramic / lubricant : water
and detergentOn flat 0,41 (>0,32) - On the heel 0,30 (>0,28)SRB Test ground steel / lubricant : glycerine
On flat 0,18 (>0,18) - On the heel: 0,15 (>0,13)



BASF Extra Rebound 41.5 innovative sole, with 2 layers of PU, new technology which returns over *40% energy* with every step :

• Less feeling of fatigue during prolonged periods of activity.

BASF We create chemistry

• Extremely soft and supple support base for lightweight and optimum comfort.

Constant energy return provided over the entire surface of the foot.

Weight	Gross Weight (38):1126 g /	Net Weight (38) : 910 g
Size	35 au 39	40 au 42
Packaging	5 paires	10 paires
Box (mm)	306 x 192 x 114	
Dimensions (mm)	590 x 210 x 320	590 x 410 x 320