



Low shoe with a sporty look
Dissipative



*International patent



- Low cut 'urban sport style' safety shoe **designed with BASF's innovative High Rebound technology.**
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1.**
- Upper made of **Putek® PLUS**, highly abrasion-resistant, water-repellent and breathable, and Stark anti-abrasion. Color: black/gray.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Forefoot lining, resistant to abrasion and perspiration acids.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Lace-up fastening with 5 pairs of metal eyelets. Black lace + grey lace, 100 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Soft** footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, static electricity dissipater.
- The **FLEX-SYSTEM® S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- ALU-LITE® B** toe-cap in aluminium resisting an impact of an energy of 200 joules, anticorrosive material and 50% lighter than steel. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-1:2019.**



BASF Extra Rebound 41.5 innovative sole, with 2 layers of **PU**, new technology which returns over **40% energy with every step** :

- Less feeling of fatigue during prolonged periods of activity.
- Extremely soft and supple support base for lightweight and optimum comfort.
- Constant energy return provided over the entire surface of the foot.



Slip resistance tests results

EN Standard : EN ISO 20345:2022

Ceramic / Laurylsulfate de sodium
A - **0,37** ($\geq 0,31$) / B - **0,35** ($\geq 0,36$)

Exigence additionnelle **SR**
Ceramic / Glycérine
C - **0,19** ($\geq 0,19$) / D - **0,25** ($\geq 0,22$)

Weight	Gross Weight (42) : 1274 g / Net Weight (42) : 1058 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350