



High-top trainers with a sporty look
Dissipative



*International Patent



- High-safety urban sport type shoe **designed with the innovative BASF High Rebound technology.**
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1.**
- Upper made from **Putek® PLUS**, which is highly abrasion-resistant, water-repellent and breathable, and Stark anti-abrasion.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Lace-up fastening with 6 pairs of metal eyelets. Black lace + grey lace, 120 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Soft** footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™ system**, static electricity dissipater.
- The **FLEX-SYSTEM® S-type** mounting insole by Jallatte is puncture-resistant to sharp objects **up to 3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the **upper and covers 100% of the foot** for all-round protection.
- ALU-LITE® B** toe-cap in aluminium resisting an impact of an energy of 200 joules, anticorrosive material and 50% lighter than steel. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-1:2019.**



Semelle **High Rebound Elastopan de BASF** en bi-composant **PU/PU**, nouvelle technologie qui garantit un **retour d'énergie de plus de 40% pendant la phase de soutien et la poussée du pied** :



- Reduced feeling of fatigue due to posture.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.

Slip resistance tests results EN Standard : EN ISO 20345:2022

Ceramic / Laurylsulfate de sodium
A - **0,37** ($\geq 0,31$) / B - **0,35** ($\geq 0,36$)

Exigence additionnelle **SR**
Ceramic / Glycérine
C - **0,19** ($\geq 0,19$) / D - **0,25** ($\geq 0,22$)

Weight	Gross Weight (42) : 1352 g / Net Weight (42) : 1124 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	335 x 210 x 130		335 x 245 x 130	
Dimensions (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356