

S3 CI SRC  
EN ISO 20345:2011  
35 to 48

Low shoe  
Dissipative



- Urban sport style safety shoe made with a **technology that combines performance and lightness**. Black and orange colours.
- **Putek® STAR** textile upper, high resistance to abrasion, waterproof and breathable. Scuff-resistant protective reinforcement to vamp.
- Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3 and EN 61340-5-1**.
- **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Closure by laces. Black Laces and one orange lace in the box. 100 cm .
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- **SOFT LIGHT** insole made of **ultra-light expanded polymer**, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **ALU-LITE®** 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.



- Polyurethane sole.
- **Special low-density comfort PU formulation.**
  - Lighter but as good as conventional polyurethane.
  - Guarantees a better 'durability/weight' ratio.
  - **Unequalled feeling of lightness.**
  - **Suitable for environments with few constraints.**
  - **Good resistance to oils and hydrocarbons.**

**Slip resistance tests results**  
EN Standard : EN ISO 20345 : 2011  
**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,38** (>0,32) - On the heel **0,38** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,30** (>0,18) - On the heel: **0,26** (>0,13)

Weight	Gross weight (42) : 1140 g / Net weight (42) : 934 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359