



S1PS CI FO SR
EN ISO 20345:2022
35 to 48

Low shoe with a sporty look
Dissipative



- Urban sport safety shoe designed **with a technology that combines performance and lightness**, black color.
- **Ultra-light, highly breathable textile** upper. Anti-abrasion reinforcement on the front.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- **3D.LINING®** lining made of 3-layer material for better moisture transport to the outside, high breathability and quick drying.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Fastening by lacing. Black shoelace 100 cm plus a gray shoelace in the box.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system (Patent pending).
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- The **FLEX-SYSTEM® S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- **ALU-LITE® B** toe-cap in aluminium resisting an impact of an energy of 200 joules, anticorrosive material and 50% lighter than steel. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-1:2019**.



- Polyurethane outer sole.
- **Special low-density PU** comfort formulation.
 - Lighter but just as effective as conventional polyurethane.
 - Guarantees a better 'durability/weight' ratio.
 - **Unequalled feeling of lightness.**
 - **Suitable for environments with few constraints.**
 - Good resistance to oils and hydrocarbons.

Slip resistance tests results

EN Standard : EN ISO 20345:2022

Ceramic / Laurylsulfate de sodium
A - **0,42** ($\geq 0,31$) / B - **0,45** ($\geq 0,36$)

Exigence additionnelle SR

Ceramic / Glycérine
C - **0,21** ($\geq 0,19$) / D - **0,24** ($\geq 0,22$)

Weight	Gross Weight (42) : 1140 g / Net Weight (42) : 934 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		335 x 210 x 130	
Dimensions (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356