

FULMAR DM10064

S3 SRC
EN ISO 20345:2011
38 to 48

Hight shoe
Nubuck leather



- ④ Grey sporty urban safety shoes, extremely lightweight.
- ④ Water-repellent nubuck leather upper.
- ④ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ④ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ④ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ④ Lace up by laces 120 cm. Two pairs of laces grey / green.
- ④ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ④ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- ④ Stab-proof non-metallic **FLEX-SYSTEM®** liner : total protection of the sole of the foot.
- ④ **Alu-Lite tip in aluminium** resisting an impact of an energy of **200 joules**.

DIAMONT Sole in PU dual density **BASF** last generation :

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatility
- ▶ Absorption of heel impact > 20 joules
- ▶ Streamlined profile rising towards the toes



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC**
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,40** (>0,32) – On the heel **0,40** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,18** (>0,18) – On the heel : **0,16** (>0,13)

Weight	Gross weight (42) : 1228 g / Net weight (42) : 1000 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359