



**metal
FREE**

**AVANGER
DM10184**

**S3 CI SRC
EN ISO 20345:2011
35 to 47**

**Hight shoe
Putek® textile**

PU Tek PLUS*
HYPERTEX technology

STARK®

3DLining

**Light
PLUS**

**VENTO
PLUS**

**FLEXsystem
ZERO**

- ⦿ Black and grey sporty urban safety shoes, extremely lightweight.
- ⦿ Putek® PLUS textile upper, high resistance to abrasion, heel in Stark® anti -abrasion.
- ⦿ 3D.LINING® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⦿ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⦿ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⦿ Lace up by laces 120 cm.
- ⦿ This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a SECOSOL® orthopaedic insole.
- ⦿ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⦿ Complete VENTO-PLUS® anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- ⦿ Stab-proof non-metallic FLEX-SYSTEM® liner : total protection of the sole of the foot.
- ⦿ LIGHT-PLUS® protective toecap in synthetic material offering protection from an impact of 200 J.



DIAMONT Sole in PU dual density BASF last generation :

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatility
- ▶ Absorption of heel impact > 20 joules
- ▶ Streamlined profile rising towards the toes

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 Requirement SRC
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,40** (>0,32) – On the heel **0,40** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,18** (>0,18) – On the heel: **0,16** (>0,13)



Weight	Gross weight (42) : 1108 g / Net weight (42) : 880 g			
Size	35 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)		340 x 210 x 133	340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359