



SPITFIRE DM20026

S1P SRC EN ISO 20345:2011 35 to 48

Low safety shoe Perforated suede leather









- @ Grey sporty urban safety shoes, extremely lightweight.
- Suede leather upper. Perforated quarters for better foot ventilation. Grey Color.
- Q 3D.LINING® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Q Lace up on 5 pairs of metal eyelets. Two laces 100 cm verde and grey.
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Soft+ Gel footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the Link ESD™ system, an innovative multicontact static electricity dissipater (Patent pending).
- FLEX-SYSTEM® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 22568-4: 2021.
- ALU-LITE® tip in aluminium resisting an impact of an energy of 200 joules.

DIAMONT Sole in PU dual density **BASF** last generation:

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatilitY
- ▶ Absorption of heel impact > 20 joules
- ▶ Streamlined profile rising towards the toes

Slip resistance tests results EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)

SRA Test ground: ceramic / lubricant: water and detergent On flat 0,40 (>0,32) - On the heel 0,40 (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat 0,18 (>0,18) - On the heel: 0,16 (>0,13)



Weight	Gross weight (42): 1176 g / Net weight (42): 960 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359