



SPITFIRE DM20026

S1P SRC
EN ISO 20345:2011
35 to 48

Low safety shoe
Perforated suede leather



- ⊗ Grey sporty urban safety shoes, extremely lightweight.
- ⊗ Suede leather upper. Perforated quarters for better foot ventilation. Grey Color.
- ⊗ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Lace up on 5 pairs of metal eyelets. Two laces 100 cm verde and grey.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ **Memory + Gel** footbed made of heat-sensitive memory foam and a gel insert to optimise the anti-fatigue effect and shock absorption in the heel area. Anatomical, perforated and dissipative.
- ⊗ **FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ⊗ **ALU-LITE**® tip in aluminium resisting an impact of an energy of 200 joules.

DIAMONT Sole in PU dual density **BASF** last generation :

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatility
- ▶ Absorption of heel impact > 20 joules
- ▶ Streamlined profile rising towards the toes



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 Requirement **SRC**
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,40** (>0,32) – On the heel **0,40** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,18** (>0,18) – On the heel: **0,16** (>0,13)

Weight	Gross weight (42) : 1176 g / Net weight (42) : 960 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359