



SHRIKE DM20164

S3 CI SRC EN ISO 20345:2011 38 to 47

> Low shoe **Nubuck leather**

STARK[®]









- Black and grey sporty urban safety shoes, extremely lightweight.
- Water-repellent nubuck leather upper, heel and front in Stark® anti -abrasion.
- @ 3D.LINING® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Q Lace up by laces 100 cm.
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- @ Complete VENTO-PLUS® anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- @ Stab-proof non-metallic FLEX-SYSTEM® liner: total protection of the sole of the foot.
- LIGHT-PLUS protective toecap in synthetic material offering protection from an impact of 200 J.

DIAMONT Sole in PU dual density **BASF** last generation:

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatilitY
- ▶ Absorption of heel impact > 20 joules
- Streamlined profile rising towards the toes

Slip resistance tests results

EN Standard: EN ISO 20345: 2011 Requirement SRC (SRA+SRB)

SRA Test ground: ceramic / lubricant: water and detergent On flat **0,40** (>0,32) + On the heel **0,40** (>0,28)

> SRB Test ground steel / lubricant : glycerine On flat **0,18** (>0,18) – On the heel: **0,16** (>0,13)



Weight	Gross weight (42): 1086 g / Net weight (42): 870 g			
Size	38 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359