







ROTOR ESD DM20194

S3 SRC EN ISO 20345:2011 38 to 47

Loe safety shoe Dissipative











- Black sporty urban safety shoes with Fit Système Boa®, extremely lightweight. Black color.
- Putek® textile upper, high resistance to abrasion, heel in Stark® anti-abrasion. Scuff-resistant inserts.
- 3D.LINING* in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Q Lace up by Fit Système Boa® on 3 pairs of lace stays.
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Soft+ Gel footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the Link ESD™ system, an multi-contact static electricity dissipater (Patent pending).
- FLEX-SYSTEM® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 22568-4: 2021.
- ALU-LITE® tip in aluminium resisting an impact of an energy of 200 joules.

DIAMONT Sole in PU dual density **BASF** last generation:

- Resists oils and hydrocarbons
- Linear profile, comfort, lightness and versatilitY
- ▶ Absorption of heel impact > 20 joules
- Streamlined profile rising towards the toes



Slip resistance tests results EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)

SRA Test ground: ceramic / lubricant: water and detergent
On flat 0,40 (>0,32) - On the heel 0,40 (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat 0,18 (>0,18) - On the heel: 0,16 (>0,13)

Weight	Gross weight (4	Gross weight (42): 1066 g / Net weight (42): 850 g			
Size	38 to 39	40 to 41	42 to 45	46 to 47	
Packaging	5 pairs	10 pairs		5 pairs	
Box shoes (mm)	340 x 2	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359	