



NOVARA
52801

S1P SRC
EN ISO 20345:2011
35 to 48

Low shoe
Suede leather



ESSENTIAL

- ❖ Low safety shoe.
- ❖ Suede leather, thickness 1,9 / 2,1. Grey color. Perforated quarters and top of upper for better foot ventilation
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Padded collar with compact flexible foam for extra comfort.
- ❖ Lined tongue with side bellows to keep out dust and dirt.
- ❖ Lace up on 3 pairs of lace stays. Laces 90 cm.
- ❖ **DIGO-FRESH** Initial hygiene layer covering the whole surface of the foot, removable, antistatic.
- ❖ **Stainless rustproof steel midsole.**
- ❖ **200 Joules safety steel toe cap.**

Outsole in dual density PU :

- Highly resistant to oils and hydrocarbons.
- Wraps round the foot for increased stability when walking.
- Deep self-cleaning and multi-directional treads.
- Heel shock absorption > 20 Joules.

Weight	Gross weight (42) : 1434 g / Net weight (42) : 1200 g		
Size	38 à 39	40 à 45	46 à 48
Packaging	5 pairs	10 pairs	5 pairs
Dimensions (mm)	340 x 375 x 700	340 x 750 x 700	340 x 375 x 700
Dimensions box (mm)	365 x 320 x 133		

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant
: water and detergent
On flat **0,34** (>0,32)
On the heel **0,28** (>0,28)

SRB Test ground steel / lubricant :
glycerine
On flat **0,20** (>0,18)
On the heel: **0,15** (>0,13)