



JASMINE IA211

S2 SRC
EN ISO 20345:2011
35 to 46

Low shoe
Antistatic

VIGOREX

* Brevet International Déposé



- Low safety shoe of loafer type designed with **anti-fatigue technology**, color white
- Synthetic **WAT-OUT®** upper, optimal breathability, water resistant and antiallergenic. Washable in soap and water.
- Upper lined in breathable textile OVER DRY, very resistant and better foot ventilation.
- Vamp lined in non-woven fabric.
- Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- CONFORTPLUS®** footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.



Semelle VIGOREX in bi-ingredient PU / and insert in E-TPU Expanded Thermoplastic PolyUrethane called Infinergy® of BASF

- E-TPU insert at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.
 - Exceptional resilience (high capacity to return energy).

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,77** (>0,32) – On the heel **0,64** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,30** (>0,18) – On the heel: **0,22** (>0,13)

Weight	Gross Weight (42) : 1110 g / Net Weight (42) : 902 g			
Size	35 - 39	40 - 41	42 - 45	46
Packaging	5 pairs	10 pairs	5 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359