



Low-top women's shoe with a sporty look
Dissipative



*International patent



- Urban sport safety shoe designed **with anti-fatigue technology**.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- Upper in technical textile, imitation Jean canvas and velvet leather, blue.
- Lining in **OVER DRY** technical textile, designed for long-lasting strength and excellent breathability.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Lacing with 5 pairs of metal eyelets. Grey laces : 120 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Soft** footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, static electricity dissipater.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- The **FLEX-SYSTEM® S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- ALU-LITE® B** toe-cap in aluminium resisting an impact of an energy of 200 joules, anticorrosive material and 50% lighter than steel. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-1:2019**.



VIGOREX insole in bi-component **PU** / and insert in **E-TPU** called **Infinergy®** from **BASF**

► **E-TPU** insert at low density of **0.25**.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to restore energy).

Infinergy®

Made with Infinergy by BASF

Slip resistance tests results
EN Standard : EN ISO 20345:2022

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,53** ($\geq 0,31$) – On the heel **0,43** ($\geq 0,36$)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** ($\geq 0,19$) – On the heel: **0,26** ($\geq 0,22$)

Weight	Gross weight (42) : 1240 g / Net weight (42) : 1032 g		
Size	35 to 39	40	41 to 42
Packaging	5 pairs	10 pairs	
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130
Cartons (mm)	592x212x313	592x410x313	685x440x356