



**KYRA
IA216**

**S3 CI SRC
EN ISO 20345:2011
35 to 42**

**Low safety women shoe of urban sport type
Antistatic**

VIGOREX

* Brevet International Déposé



- Low safety shoe of urban sport type designed with anti-fatigue technology.
- Nubuck leather upper . Grey color.
- Upper lined in breathable textile OVER DRY, very resistant and better foot ventilation .
- Vamp lined in non-woven fabric.
- Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- Closure by laces. Laces : 120 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- COMFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ALU-LITE**® tip in aluminium resisting an impact of an energy of 200 joules.



Semelle VIGOREX in bi-ingredient PU / and insert in E-TPU Expanded Thermoplastic PolyUrethane called Infinergy® of BASF

► E-TPU insert at low density of 0.25.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to return energy).



Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,77** (>0,32) – On the heel **0,64** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** (>0,18) – On the heel: **0,22** (>0,13)

Weight	Gross Weight (38) : 1346 g / Net Weight (38) :1138 g	
Size	35 au 39	40 au 42
Packaging	5 paires	10 paires
Box (mm)	306 x 192 x 114	
Dimensions (mm)	590 x 210 x 320	590 x 410 x 320