

# JALCERES SAS ESD JHJH301



**S1P SRC**  
**EN ISO 20345:2011**  
**38 to 48**



Link-ESD



- **Suede leather .**
- **Extra Rebound sole en Elastopan de BASF.**
- **Aluminum safety toe cap type B and midsole no metallic.**
- **Dissipative.**

\* Brevet International Déposé

- ❖ Urban sport style safety shoe designed with **BASF's innovative High Rebound technology.**
- ❖ Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1.**
- ❖ Suede leather. Perforated quarters and top of upper for better foot ventilation. TPU insert at the heel integrated in the lacing for good holding of the foot in the shoe.
- ❖ Breathable upper lining in **3D** mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on 2 pairs of metal eyelets and 3 pairs of quick unlacing. Lace-loop to keep tongue in place as you walk. Laces 100 cm from 38 to 40 and 120 cm from 41 to 48.
- ❖ Tabs at the back for easy pull-on.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative multi-contact static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ **PREM-Alu** tip in aluminium type B resisting an impact of an energy of 200 joules. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with Standard 22568-1 : 2021.
- ❖ New manufacturing process : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection. **100% composite** materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **BASF Extra Rebound 41.5** innovative sole, with 2 layers of PU, new technology which returns over **40% energy** with every step.



<b>Slip resistance tests results</b>	
EN Standard : EN ISO 20345 : 2011	
<b>Requirement SRC (SRA+SRB)</b>	
<b>SRA</b> Test ground : ceramic / lubricant : water and detergent	
On flat <b>0,41</b> (>0,32) – On the heel <b>0,30</b> (>0,28)	
<b>SRB</b> Test ground steel/lubricant : glycerine	
On flat <b>0,18</b> (>0,18) – On the heel <b>0,15</b> (>0,13)	



- Extremely soft and supple support base for lightweight and optimum comfort.
- Constant energy return provided over the entire surface of the foot.
- Less feeling of fatigue during prolonged periods of activity.
- Raised design encouraging liquid run-off.

Weight	Gross weight (42) : 1350 g / Net weight (42) : 1134 g			
Size	38 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	695 x 227 x 366	685 x 423 x 347	685 x 500 x 347	685 x 250 x 346

