

JALMETIS SAS ESD

JHJH308



S3 CI SRC
EN ISO 20345:2011
35 to 48



* Brevet International Déposé

- **Textil Putek® PLUS and anti abrasion.**
- **High Rebound sole en Elastopan de BASF.**
- **Aluminum safety toe cap and midsole no metallic.**
- **Dissipative.**

- ❖ Urban sport style safety shoe designed with **BASF's innovative High Rebound technology.**
- ❖ Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1.**
- ❖ Textil **Putek® PLUS** and anti abrasion. TPU insert at the heel integrated in the lacing for good holding of the foot in the shoe.
- ❖ Breathable upper lining in **3D mesh**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on 2 pairs of metal eyelets and 3 pairs of quick unlacing. Lace-loop to keep tongue in place as you walk. Laces 100 cm from 38 to 40 and 120 cm from 41 to 48.
- ❖ Tabs at the back for easy pull-on.
- ❖ **Memory GEL ESD** footbed made from **BASF Elastopan polyurethane** and heat-sensitive memory foam cushions pressure points, improves weight distribution and absorbs vibrations in the heel area. Anatomically formed and perforated.
- ❖ **PREM-Alu** tip in aluminium resisting an impact of an energy of 200 joules.
- ❖ New manufacturing process : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- ❖ **100% composite** materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **BASF Extra Rebound 41.5** innovative sole, with 2 layers of PU, new technology which returns over **40% energy** with every step. .

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,41** (>0,32) – On the heel **0,30** (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat **0,18** (>0,18) – On the heel **0,15** (>0,13)



- Extremely soft and supple support base for lightweight and optimum comfort.
- Constant energy return provided over the entire surface of the foot.
- Less feeling of fatigue during prolonged periods of activity.
- Raised design encouraging liquid run-off.

Weight	Gross weight (42) : 1298 g / Net weight (42) : 1090 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	695 x 227 x 366	685 x 423 x 347	685 x 500 x 347	685 x 250 x 346

