



S3 CI SRC
EN ISO 20345:2011
35 to 48



- Water-repellent full-grain leather
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B and midsole no metallic



Link-ESD

- High-laced boot style outdoor incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- Scuff-resistant protective reinforcement to heel and PU reinforcement to the front of the sole.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- TPU reinforcement for better protection of the malleoli.
- Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- Lace up with four pairs of no metallic eyelets and two pairs of **Quick Lio**. Laces 150 cm.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a **soft BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESDTM system**, an innovative multi-contact, static electricity dissipater. (Patent pending).
- Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- Stab-resistant structural insole and liner in **FleXtane™ By Jallatte ESD**, in compliance with standard **22568-4 : 2021**, antistatic, **100% composite**. Sewn directly onto the upper and covering **100% of the foot for total protection**.
- Heel stiffener to reinforce the heel seat.
- Insole **PU / PU de BASF®**, design outdoor, excellent slip resistance.



Slip resistance tests results EN Standard :
EN ISO 20345 : 2011 **Requirement SRC** (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,43** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat **0,28** (>0,18) – On the heel **0,20** (>0,13)

- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.



Weight	Gross weight (42) : g / Net weight (42) : g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	687 x 226 x 350	687 x 432 x 348	689 x 511 x 351	689 x 260 x 348



www.jallatte.com