JALPYTHON ESD
JIJI244

INDUSTRY 4.0

* International patent

S3S CI FO SR
EN ISO 20345:2022
35 to 48

- **Putek® PLUS textile upper**
- **Semelle PU/PU de BASF®**
- **ESD / Dissipative**
- **Type B polymer end cap and non-metallic anti-perforation S**

- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™ anti-fatigue technology** designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- **Putek® PLUS** textile upper, high resistance to abrasion, water repellent and breathable . Abrasion-resistant eyelet holder and heel. Reflective insert at the heel. Colour : black.
- Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Closed by **BOA® Fit System**, delivers micro-adjustable, precision fit engineered to perform in the toughest conditions. The **BOA® Fit System** is **guaranteed** for the lifetime of the product on which it is integrated.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact, static electricity dissipater.

- **Ergonomic shoe** with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- **The FleXtane™ S-type** mounting insole **by Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- Heel stiffener to reinforce the heel seat.
- **BASF® PU/PU sole** with an urban sport design, linear profile and excellent slip resistance.

Slip resistance tests results EN Standard ISO 20345:**2022**
Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,35** (≥ 0,31)
B- Front to back **0,40** (≥ 0,36)

Additionnal requirement **SR :** Ceramic /Glycerin
C - Heel to the front **0,22** (≥ 0,19)
D- Front to back **0,27** (≥ 0,22)

BASF We create chemistry

- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Weight	Gross weight (42) : 1336 g / Net weight (42) : 1120 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130	
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356

Jallatte®
www.jallatte.com

Document non contractuel
Copyright JALLATTE
Diffusion Controlée

03/04/2026