

S2 FO SR  
EN ISO 20345:2022  
35 to 48



Link-ESD

ASEPTANE



- Microfiber Aseptane™
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B

- Safety shoe type loafer incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- White **Aseptane™** upper with microfiber resin combines optimal breathability and unmatched watertightness.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™ system**, an innovative multi-contact, static electricity dissipater.
- Ergonomic shoe** with broad toe-cap **SPRINTANE** type **B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- Heel stiffener to reinforce the heel seat.



- BASF® PU / PU sole** with an urban sport design, linear profile and excellent slip resistance.

## Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,39** ( $\geq 0,31$ )

B- Front to back **0,40** ( $\geq 0,36$ )

Additional requirement **SR** : Ceramic /Glycerin

C - Heel to the front **0,26** ( $\geq 0,19$ )

D- Front to back **0,26** ( $\geq 0,22$ )



- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Poids	Brut (42) : 1316 g / Net (42) : 1100 g			
Pointure	35 au 39	40	41 au 45	46 au 48
Conditionnement	5 paires	10 paires		5 paires
Boîtes (mm)	306 x 192 x 114		335 x 210 x 130	
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356



www.jallatte.com