



S3 CI SRC
EN ISO 20345:2011
35 to 48



- Water-repellent full-grain leather
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B and midsole no metallic

Link-ESD

- Safety shoe style outdoor incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- Scuff-resistant protective reinforcement to heel and PU reinforcement to the front of the sole.
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- Lace up with four pairs of no metallic eyelets. Laces 100 cm.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a **soft BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESDTM system**, an innovative and seamless, multi-contact, static electricity dissipater. (Patent pending).
- Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard 22568-2:2019.
- Stab-resistant structural insole and liner in **FleXtane™ By Jallatte ESD**, in compliance with standard 12568:2010, antistatic, **100% composite**. Sewn directly onto the upper and covering **100% of the foot for total protection**.
- Heel stiffener to reinforce the heel seat.
- Insole **PU / PU de BASF®**, design outdoor, excellent slip resistance.



- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.



Slip resistance tests results	EN Standard :			
	EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)			
SRA Test ground : ceramic / lubricant : water and detergent	On flat 0,43 (>0,32) – On the heel 0,31 (>0,28)			
SRB Test ground steel/lubricant : glycerine	On flat 0,28 (>0,18) – On the heel 0,20 (>0,13)			

Weight	Gross weight (42) : g / Net weight (42) : g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	687 x 226 x 350	687 x 432 x 348	689 x 511 x 351	689 x 260 x 348

