

OB A E WRU FO SRC
EN ISO 20347:2012
Du 35 au 48



0%
METAL

ASEPTANE
Link-ESD

ASSEMBLÉ
EN
FRANCE



Work clogs for professional use
(No toe cap and anti-perforation inner sole)

- ❖ Soft and lightweight safety clog with no toe cap and anti-perforation inner sole **designed with anti-fatigue technology**. Upper and sole assembled in France. white and grey color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- ❖ Microfibre upper, easily washable with soapy water, good splash resistance.
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Top of instep is padded for enhanced comfort.
- ❖ Elasticated strap fastening for easier adjustment and better grip of the foot. Strap can be folded over the top of the foot and removed using the popper system on the side.
- ❖ **Soft + Gel** footbed made of **BASF Dynamic** PU with heat **sensitive memory foam** and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ Support around the heel to ensure a good grip of the foot.
- ❖ **Innovative J-Energy triple-density sole** in dual-component **PU/E-TPU** insert Expanded Thermoplastic PolyUrethane known as **Infinergy®** from **BASF**, with an extraordinary capacity to return more than **55%** of the energy accumulated during walking to reduce fatigue and lower the risk of musculoskeletal disorders in the lower limbs (according to standard **EN ISO 8307**).



www.infinergy.basf.com

Infinergy®

Made with Infinergy® by BASF

Slip resistance tests results EN Standard ISO 20345:2012

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,62 (>0,32)**

B- Front to back **0,48 (>0,28)**

Additionnal requirement SR : Ceramic /Glycerin

C - Heel to the front **0,23 (>0,18)**

D- Front to back **0,19 (>0,13)**

- Polyurethane outer sole.
- **E-TPU insert** at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.

Dynamic performance in 3 phases: Shock Absorption – Accumulation of energy - Dynamic Return.

Weight	Gross weight (37) : 856 g / Net weight (37) : 640 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	695 x 227 x 366	685 x 423 x 347	685 x 500 x 347	685 x 250 x 346



Jallatte®

www.jallatte.com