

Work loafer for professional use

(No toe cap, no anti-perforation)

J-PRO 347



JOJO210 JALBOSS ESD

EN ISO 20347 : 2012 O2 FO SRC

35 to 48



0% METAL



Link-ESD



- ❖ Work loafer for professional use, designed with **anti-fatigue technology**, no toe cap or anti-perforation sole. Upper and sole assembled in France. Black color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- ❖ **Putek® PLUS** textile upper, high resistance to abrasion, water repellent and breathable. Anti abrasion insert. **TPU insert** built-in to the laces, ensuring an effective heel grip, enhanced alignment of the foot in the shoe and protection against any sprains.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded tongue for good instep protection.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Elasticated fastening for easy adjustment around the ankle joint.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Innovative **J-energy** sole in bi-ingredient PU / and **BASF Infinergy® E-TPU** (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 55% of the **energy accumulated** while walking in order to reduce fatigue and to prevent RSIs to the legs.



- Outsole in Polyuréthane.
- E-TPU insert at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.
 - **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return**



Slip resistance tests results	
EN Standard :	EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)
SRA Test ground :	ceramic / lubricant : water and detergent
	On flat 0,62 (>0,32) – On the heel 0,48 (>0,28)
SRB Test ground steel/lubricant :	glycerine
	On flat 0,23 (>0,18) – On the heel 0,19 (>0,13)

Weight	Gross weight (42) : 916 g / Net weight (42) : 700 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350

