

JALPEARL ESD JQJQ204

J-QUARTZ



S3S CI LG FO SR
EN ISO 20345:2022 + A1:2024
35 to 48



Air&Shock

Xetane B

- Upper in microfibre
- Dissipative
- J-Quartz polyurethane sole
- Xetane B composite toe cap and midsole no metallic S

- Versatile urban sport safety shoe incorporating the latest safety standards, black color.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3 / 4-5 / 5-1**.
- Water-repellent microfibre upper, nubuck look.
- Breathable upper lining in **3D SURF**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Fastens by 5 pairs of non metallics eyelets. 120 cm flat black lace and a second colored lace included in the box.
- Thermo-regulating, ergonomic **Air&Shock** insole. Its air evacuation channel structure and perforations improve climatic comfort in the shoe, while its two-material design ensures optimum comfort when walking.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- Composite toe-cap **Xétane B** bi-material resin with fibrous reinforcement resistant to 200J. Amagnetic and athermic. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.
- The **FlexTane™ S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and covers **100% of the foot** for all-round protection.
- Heel stiffener to reinforce the heel seat.
- J-Quartz sole** in bi-density PolyUrethane, fitted with the **JAL'GRIP** system, an **LG-standard** double unhooked heel for good grip on ladder rungs and maximum safety when working at height.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,39** ($\geq 0,31$)

B- Front to back **0,42** ($\geq 0,36$)

Additionnal requirement SR : Ceramic /Glycerin

C - Heel to the front **0,24** ($\geq 0,19$)

D- Front to back **0,25** ($\geq 0,22$)

► Polyurethane outer sole bi-density :

- High resistance to abrasion and stretching..
- Heel shock absorbtion ≥ 20 joules.
- Double unhooked heel with ≥ 35 mm camber zone and ≥ 1.5 mm deep transverse studs.
- Comfort layer in 0.45 density polyurethane for greater flexibility and good shock and vibration absorption.



www.jallatte.com

Weight	Gross weight (42) : 1382 g / Net weight (42) : 1166 g	
Size	35 to 42	43 to 48
Packaging	10 pairs	
Box shoes (mm)	335 x 210 x 130	335 x 244 x 130
Cartons (mm)	685 x 440 x 356	680 x 514 x 356