

# JALTORNADO ESD

## JVJV111



S3S CI FO SR  
EN ISO 20345:2022  
35 to 48



Link-ESD



ASSEMBLÉ  
EN  
FRANCE



- Microfiber upper
- PU/PU BASF® sole
- ESD / Dissipative
- Aluminum safety toe cap type B and midsole no metallic S

- ❖ Low safety shoe urban sport type designed with **technology combining performance and lightness**, black color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3/4-5/5-1**.
- ❖ Water-repellent microfiber upper, nubuck look. Reflective tape at the heel.
- ❖ Breathable upper lining in **3D mesh**, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the shoes.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Closed by **BOA® Fit System**, delivers micro-adjustable, precision fit engineered to perform in the toughest conditions. The **BOA® Fit System** is **guaranteed** for the lifetime of the product on which it is integrated.
- ❖ **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ **PREM-Alu** tip in aluminium **type B** resisting an impact of an energy of 200 joules. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with Standard **22568-1:2019**.
- ❖ Insole and anti-puncture midsole in non-woven **FLEX-LIGHT By Jallatte**, **54% lighter than a standard insert, complies with standard 22568-4:2021**, antistatic, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Innovative HELIUM sole** in bi-component **PU LIGHT/ PU** from **BASF®**, specially formulated for an incomparably light feel and absolute comfort.

### Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)  
A- Heel to the front **0,40** ( $\geq 0,31$ )  
B- Front to back **0,38** ( $\geq 0,36$ )

Additional requirement **SR** : Ceramic / Glycerin  
C - Heel to the front **0,25** ( $\geq 0,19$ )  
D - Front to back **0,23** ( $\geq 0,22$ )

- Polyurethane outsole.
- **Special low-density PU comfort formulation.**
  - Lighter but just as effective as conventional polyurethane.
  - Guarantees a better 'durability/weight' ratio.
  - **Unequaled feeling of lightness.**
  - **Suitable for working environment with few constraints.**
  - Good resistance to oils and hydrocarbons.

Weight	Gross weight (42) : 1336 g / Net weight (42) : 1120 g			
Size	35 au 39	40 au 42	43 au 45	46 au 48
Packaging	5 pairs		10 pairs	
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	365 x 260 x 133
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	695 x 276 x 385



**Jallatte®**

www.jallatte.com