

JALWING SAS ESD JVJV202



S3 CI SRC
EN ISO 20345:2011
35 to 48



Link-ESD

- **Microfiber upper**
- **PU/PU BASF® sole**
- **ESD / Dissipative**
- **Aluminum safety toe cap type B and midsole no metallic**

- ❖ Low safety shoe urban sport type designed with **technology combining performance and lightness**, black color.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II** tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- ❖ Water-repellent microfiber upper, nubuck look. Reflective tape at the heel.
- ❖ Breathable upper lining in **3D** mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on 4 perforations and one pair of non-metallic eyelets. Flat lace 100 cm.
- ❖ **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ **PREM-Alu** tip in aluminium type B resisting an impact of an energy of 200 joules. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard 22568-1 : 2021.
- ❖ Insole and anti-puncture midsole in non-woven **FLEX-LIGHT By Jallatte**, **54% lighter than a standard insert, complies with standard 22568-4 : 2021**, antistatic, sewn directly onto the upper and covers **100% of the foot** for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Innovative HELIUM sole** in bi-component **PU LIGHT/ PU** from **BASF®**, specially formulated for an incomparably light feel and absolute comfort.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC (SRA+SRB)**

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,39** (>0,32) – On the heel **0,40** (>0,28)

SRB Test ground steel/lubricant : glycerine

On flat **0,29** (>0,18) – On the heel **0,27** (>0,13)

- Polyurethane outsole.
- **Special low-density PU comfort formulation.**
 - Lighter but just as effective as conventional polyurethane.
 - Guarantees a better 'durability/weight' ratio.
 - **Unequaled feeling of lightness.**
 - **Suitable for working environment with few constraints.**
 - Good resistance to oils and hydrocarbons.

Weight	Gross weight (42) : 1106 g / Net weight (42) : 900 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	695 x 227 x 366	685 x 423 x 347	685 x 500 x 347	685 x 250 x 346



www.jallatte.com