JALWING ESD
JVJV202

S3S CI FO SR
EN ISO 20345:2022
35 to 48

LiNK-ESD

HELIUM 2

ASSEMBLÉ EN FRANCE

*International Patent

- **Microfibre Light upper**
- **PU/PU sole from BASF®**
- **ESD / Dissipative**
- **Type B aluminum tip and non-metallic anti-perforation S**

- Urban sport safety shoe **designed with a technology that combines performance and lightness**, in black and grey.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1.**
- Water-repellent microfibre upper, nubuck look. Reflective trim at heel.
- Breathable **3D SURF mesh** upper lining with honeycomb structure, improves peripheral ventilation of the foot and dries quickly.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Lacing closure system with 4 perforations and a pair of non-metallic eyelets. Flat lace 100 cm.
- **SOFT LIGHT** hygiene insole in ultra-lightweight expanded polymer, cushions pressure points, improves weight distribution and absorbs heel impact. Anatomically shaped, perforated and equipped with the innovative **Link ESD™** multi-contact static dissipation system (Patent pending).
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- **PREM-Alu B** toe-cap in aluminium resisting an impact of an energy of 200 joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with **Standard 22568-1:2019**.
- Antiperforation inner sole and insert in non-woven textile **FLEX-LIGHT By Jallatte S type** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with **standard 22568-4:2021,** 54% lighter than a standard insert, antistatic, sewn directly onto the upper and **covering 100% of the foot** for total protection.
- Heel stiffener to reinforce the heel seat.
- **Innovative HELIUM sole** in bi-component **PU LIGHT/ PU from BASF**, specially formulated for an incomparably light feel and absolute comfort.

Slip resistance tests results EN Standard ISO 20345:**2022**
Test ground : Ceramic / NaLS (Sodium lauryl sulfate)
A- Heel to the front **0,40** (≥0,31)
B- Front to back **0,38** (≥0,36)

Additionnal requirement **SR :** Ceramic /Glycerin
C - Heel to the front **0,25** (≥0,19)
D- Front to back **0,23** (≥0,22)

- Polyurethane outsole.
- **Special low-density PU comfort formulation**.
  - Lighter but just as effective as conventional polyurethane.
  - Guarantees a better 'durability/weight' ratio.
  - **Unequalled feeling of lightness.**
  - **Suitable for environments with few constraints**.
  - Good resistance to oils and hydrocarbons.

Weight	Gross weight (42) : 1256 g / Net weight (42) : 1040 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	365 x 260 x 133
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	695 x 276 x 385

Jallatte®

www.jallatte.com

Document non contractuel
Copyright JALLATTE
Diffusion Controlée

20/04/2026