



JY104 JALPULSE SAS ESD

S3 CI SRC
EN ISO 20345:2011
38 to 48



* Brevet International

- Water-repellent full-grain leather / textile
- J-ENERGY sole Infinergy® de BASF
- Aluminum safety toe cap type B and midsole no metallic
- Dissipative

- High safety shoe of urban sport type designed with anti-fatigue technology.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.
- Water-repellent full-grain leather and déperlant textiles upper. TPU insert built-in to the laces, ensuring an effective heel grip, enhanced alignment of the foot in the shoe and protection against any sprains.
- Micro-aerated mesh lining, smooth appearance, 3 layer structure combining a textile mesh, a foam and a reinforcing grid. High mechanical strength (abrasion and tearing) and fast drying.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on seven pairs of eyelets. Leather lace-loop keeps tongue in place as you walk. Black laces : 160 cm.
- Tabs at the back for easy pull-on.
- Soft+ Gel footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the Link ESD™ system, an innovative multi-contact static electricity dissipater (Patent pending).
- This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a SECOSOL® orthopaedic insole.
- PREM-Alu tip in aluminium type B resisting an impact of an energy of 200 joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard 22568-1 : 2021.
- New manufacturing process : antiperforation inner sole and insert in FlexTane™ By Jallatte material, antistatic, 100% composite. Sewn directly onto the bootstrap and covering 100% of the foot for all-round protection. 100% composite materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- Heel stiffener to reinforce the heel seat.
- Innovative J-energy sole in bi-ingredient PU / and BASF Infinergy® E-TPU (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 55% of the energy accumulated while walking in order to reduce fatigue and to prevent RSIs to the legs.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,62** (>0,32) – On the heel **0,48** (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat **0,23** (>0,18) – On the heel **0,19** (>0,13)

- Outsole in Polyuréthane.
- E-TPU insert at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.
 - Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return

Infinergy®

Made with Infinergy by BASF

Weight	Gross weight (42) : 1390 g / Net weight (42) : 1182 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359



 **Jallatte**®

www.jallatte.com