EU-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and in accordance with the current certification process. It has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/006/162/05/26/1101

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer: **JALLATTE SAS**
5 RUE DU FORT PIERRE JALLATTE
30170 SAINT HIPPOLYTE DU FORT France

Description

PPE Type: **protective glove against mechanical risks, thermal risks**

Product reference: **GT-840**

Glove description: **Glove with Nitrile TOPFOAMLITE coating on palm +/ reinforced nitrile thumb crotch**

Available sizes: **Taille 6 a 12**

Pictures:

Reference standard:	Levels of performance / class of protection
« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material. « 0 » indicates that the glove falls below the minimum performance level for the individual hazard.	
EN ISO 21420:2020 + A1:2024	**compliant**
EN 388:2016 + A1:2018	**4 X 4 2 D**
EN 407:2020	**X 1 X X X X**

At the date of the certificate, the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the user instructions index 01 dated from MAY 2026.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Salomé FRAU
Certification team Leader

CE MARKING DEPARTMENT CTC NB 0075 EC-Type Examination Certificate

Date of first issue: 28 May 2026
Date of end of validity: 27 May 2031

JALLATTE SAS

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	**:**	**GT-840**
Article code	**:**	**/**
Technical file index	**:**	**01**
Last update	**:**	**MAY 2026**

IDENTIFICATION

Reference of the product :	:	GT-840
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	MAY 2026

Manufacturer :

JALLATTE SAS

5 RUE DU FORT PIERRE JALLATTE

30170 SAINT HIPPOLYTE DU FORT France

tel : 0466808600
fax :

Factory :

ZHEJIANG KANGLONGDA SPECIAL PROTECTION TECHNOLOGY CO., LTD.

No.7 East Weiwu Road, Gaibei Town, Shangyu City, Zhejiang Province

China
tel: 0575-82872578
fax: 0575-82870808

KANGLONGDA VIETNAM PROTECTION TECHNOLOGY COMPANY LIMITED

Lot CN-05, Viglacera- Phong Dien Industrial Park, Phong Hoa Commune, Phong Dien District ,Thua Thien Hue Province

Vietnam
tel: 0575-82872578
fax: 0575-82870808

GLOVE DESCRIPTION

General glove description and intended use:

Glove with Nitrile TOPFOAMLITE coating on palm +/ reinforced nitrile thumb crotch

This glove is designed against mechanical risks, thermal risks.

Type of coating finish : foam

Visual description (picture back and palm sides) :

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)		
		Applicable
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒
§1.4	Manufacturer's instructions and information is available	☒
§2.5	PPE which may be caught up during use	☒
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒
§2.14	Multi-risk PPE	☒
§3.3	The PPE is intended to protect against mechanical injuries	☒
§3.6	Protection against heat and/or fire	☒

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m²)	Gauges	Thickness
Palm	HP00002	noir	Polyéthylène haute performance Goldsilk Plus	350 g/m²	18	
	NY00001	noir	Nylon			
	SP00001	gris	Spandex			
	GR00001	noir	Graphène			
	NBR0006	orange	Nitrile orange			0,2 mm
	NBR0002	noir	Nitrile TOPFOAMLITE			0,2 mm
Back	HP00002	noir	Polyéthylène haute performance Goldsilk Plus	350 g/m²	18	
	NY00001	noir	Nylon			
	SP00001	gris	Spandex			
	GR00001	noir	Graphène			
Cuff	HP00002	noir	Polyéthylène haute performance Goldsilk Plus	380 g/m²	18	
	NY00001	noir	Nylon			
	SP00001	gris	Spandex			
	GR00001	noir	Graphène			
	EL00001	noir	Elastique			
Binding	PES0002 Polyester red size 6 PES0003 Polyester pink size 7 PES0004 Polyester yellow size 8 PES0005 Polyester orange size 9 PES0006 Polyester green size 10 PES0007 Polyester blue size 11 PES0008 Polyester black size 12	red / pink / yellow / orange / green / blue / black	polyester	20 g/m²		

PROTECTION SCOPE

This product meets the essential requirements of the Personal Protective Equipment Regulation (EU) 2016/425.

This glove is designed against mechanical risks, thermal risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420:2020 + A1:2024

Dexterity : 5

Available size range: Taille 6 a 12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 + A1 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388:2016 + A1:2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	X
Tear strength resistance	4
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	D
Impact Protection	N/A

The levels of performance have been measured on the palm.

Thermal hazard EN 407:2020

Mechanical strength	
Tear strength resistance (N)	≥ 10

Thermal protections	Performance levels
Limited flame spread	X
Contact heat	1
Convective heat	X
Radiant heat	X
Small splashes of molten metal	X
Large quantities of molten metal	X

TEST REPORTS

EN ISO 21420+A1 + innocuousness	L251220334_1 L251220370_2 L251220333_3 L251220368_2
EN 388	L251220333_3 S260201387_1
EN 407	S260403961_1

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :
Logo CE
Glove's reference : GT-840
Article Code : /
Size indicator
Pictograms related to risks against which protection is offered with performance levels
Information pictogram
Address of Manufacturer :
Date of Manufacture (month/year) and/or serial/batch number :
Date of obsolescence (month/year) if applicable:

Marking example :

Method of marking on the glove :

Etiquette recto verso piquée à l'intérieur du gant et tranfert sur le dos et le poignet

Packaging suitable for transport:

1 paire par chevalet / 12 paires en sachet transaparent / 1 carton de 12 sachets de 12 paires

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

This glove is not washable.

MEANS OF CONTROL

Prélèvements aléatoires à chaque arrivage de container et envoi au CTC pour tests :
EN 388 6.3 Coupure par tranchage TDM (EN ISO 13997) et innocuité
EN 407 4.5.3 & 6.3 Chaleur de contact

INSTRUCTIONS FOR USE

JALLATTE SAS

5 RUE DU FORT PIERRE JALLATTE

30170 SAINT HIPPOLYTE DU FORT France

Glove reference : GT-840

Article code: /

User notice index : 01

Last update : MAY 2026

Glove description :

Glove with Nitrile TOPFOAMLITE coating on palm +/ reinforced nitrile thumb crotch

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

The glove meets the requirements of the standard EN ISO 21420:2020 + A1:2024 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: Taille 6 a 12

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420+A1 Annex B.

Information about marking

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

The CE marking means that this product meets the requirements of the regulation 2016/425

Mechanical hazard - EN 388:2016 + A1:2018

4 X 4 2 D

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	X	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	D	(A to F)
Impact Protection		

Thermal risk - EN 407:2020

Protection against heat without flame

X1XXXX

Levels of performance

Limited flame spread	X	(on 4 maxi)
Contact heat	1	(on 4 maxi)
Convective heat	X	(on 4 maxi)
Radiant heat	X	(on 4 maxi)
Small splashes of molten metal	X	(on 4 maxi)
Large quantities of molten metal	X	(on 4 maxi)

Read carefully the instructions for use provided with the product

Protection limit:

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear…).

No flame protection is claimed. This glove shall not be in contact with naked flame.

Mechanical protection:

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

Thermal protection against heat and flame:

The glove's area of the thermal protection is Palm.

This glove cannot be used in high-temperature environments the effects of which are comparable to those of an air temperature of at least 100 °C.

This glove provides a protection for a limited contact time with hot products.

Hand protective equipment cannot be used to handle products with a temperature over 100°C

For multilayer gloves or multilayer hands protective equipment for thermal domestic risks with different layers of material, the performance levels are warranted only for the whole product.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

This glove is not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available on : www.jallatte.fr